CHAPTER 4 – LIGHT, VENTILATION & OCCUPANCY LIMITATIONS

Chapter 4 establishes the minimum criteria for light and ventilation and identifies occupancy limitations.

* Indicates code is still under review for inclusion.

marcates code	is sell under review for melasion.				
SECTION 401 - GENERAL					
401.1 Scope.	The provisions of this chapter shall govern the minimum conditions and standards for light, <i>ventilation</i> and space for occupying a structure.				
401.2 Responsibility.	The <i>owner</i> of the structure shall provide and maintain light, <i>ventilation</i> and space conditions in compliance with these requirements. A person shall not occupy as <i>owner-occupant</i> , or permit another person to occupy, any <i>premises</i> that do not comply with the requirements of this chapter.				
401.3 Alternative devices.	In lieu of the means for natural light and <i>ventilation</i> herein prescribed, artificial light or mechanical <i>ventilation</i> complying with the <i>International Building Code</i> shall be permitted.				
SECTION 402 - LI	GHT				
402.1 Habitable spaces.	Every habitable space shall have at least one window of approved size facing directly to the outdoors or to a court. The minimum total glazed area for every habitable space shall be 8 percent of the floor area of such room. Wherever walls or other portions of a structure face a window of any room and such obstructions are located less than 3 feet (914 mm) from the window and extend to a level above that of the ceiling of the room, such window shall not be deemed to face directly to the outdoors nor to a court and shall not be included as contributing to the required minimum total window area for the room. Exception: Where natural light for rooms or spaces without exterior glazing areas is provided through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but a minimum of 25 square feet (2.33 m²). The exterior glazing area shall be based on the total floor area being served.				
402.2 Common halls and stairways.	Every common hall and stairway in residential occupancies, other than in one-and two-family dwellings, shall be lighted at all times with at least a 60-watt standard light bulb for each 200 square feet (19 m²) of floor area or equivalent illumination, provided that the spacing between lights shall not be greater than 30 feet (9144 mm). In other than residential occupancies, means of egress, including exterior means of egress, stairways shall be illuminated at all times.				
402.3 Other spaces.	All other spaces shall be provided with natural or artificial light sufficient to permit the maintenance of sanitary conditions, and the safe <i>occupancy</i> of the space and utilization of the appliances, equipment and fixtures.				
SECTION 403 - VENTILATION					
403.1	Every habitable space shall have at least one openable window. The total openable				

Draft City of Spokane Housing Quality Standards, Chapter 4

Habitable spaces.	area of the window in every room shall be equal to at least 45 percent of the minimum glazed area required in Section 402.1.					
403.2 Bathrooms and toilet rooms.	Every <i>bathroom</i> and <i>toilet room</i> shall comply with the <i>ventilation</i> requirements for <i>habitable spaces</i> as required by Section 403.1, except that a window shall not be required in such spaces equipped with a mechanical <i>ventilation</i> system. Air exhausted by a mechanical <i>ventilation</i> system from a <i>bathroom</i> or <i>toilet room</i> shall discharge to the outdoors and shall not be recirculated.					
403.3 Cooking facilities.	Unless approved through the certificate of occupancy, cooking shall not be permitted in any rooming unit and a cooking facility or appliance shall not be permitted to be present in the rooming unit. Exceptions: 1. Where specifically approved in writing by the code official. 2. Devices such as coffee pots and microwave ovens shall not be considered cooking appliances.					
403.5 Clothes dryer exhaust.	Clothes dryer exhaust systems shall be independent of all other systems and shall be exhausted outside the structure in accordance with the manufacturer's instructions. Exception: Listed and labeled condensing (ductless) clothes dryers.					
SECTION 404 – C	OCCUPANCY LIMITATIONS					
404.1 Privacy.	Dwelling units, hotel units, housekeeping units, rooming units and dormitory units shall be arranged to provide privacy and be separate from other adjoining spaces.					
404.2 Minimum room widths.	A habitable room, other than a kitchen, shall be a minimum of 7 feet (2134 mm) in any plan dimension. Kitchens shall have a minimum clear passageway of 3 feet (914 mm) between counter fronts and appliances or counter fronts and walls. Exception 1. Homes built before [YEAR]. 2. Tiny Homes					
* 404.3 Minimum ceiling heights.	Habitable spaces, hallways, corridors, laundry areas, bathrooms, toilet rooms and habitable basement areas shall have a minimum clear ceiling height of 7 feet (2134 mm). Exceptions: 1. In one- and two-family dwellings, beams or girders spaced a					
	minimum of 4 feet (1219 mm) on center and projecting a maximum of 6 inches (152 mm) below the required ceiling height.					
	 Basement rooms in one- and two-family dwellings occupied exclusively for laundry, study or recreation purposes, having a minimum ceiling height of 6 feet 8 inches (2033 mm) with a minimum clear height of 6 feet 4 inches (1932 mm) under beams, girders, ducts and similar obstructions. 					

Draft City of Spokane Housing Quality Standards, Chapter 4

	3.	and having a slope minimum clear ce one-third of the re area of such room	ed ceiling over all iling height of 7 f equired minimun s, only those por	eping, study or simil or part of the room feet (2134 mm) over n floor area. In calcu tions of the floor are feet (1524 mm) shall	, with a a minimum of lating the floor ea with a				
* 404.4	Every bedroom and living room shall comply with the requirements of Sections								
Bedroom and	404.4.1 through 404.4.5.								
living room requirements.	404.4.1 Room area. Every living room shall contain at least 120 square feet								
, equilibrium.	(11.2 m²) and every bedroom shall contain a minimum of 70 square feet (6.5 m²) and								
	every bedroom occupied by more than one person shall contain a minimum of 50								
	square feet (4.6 m ²) of floor area for each occupant thereof. 404.4.2 Access from bedrooms. <i>Bedrooms</i> shall not constitute the only means								
	of access to other bedrooms or habitable spaces and shall not serve as the only								
	means of egress from other <i>habitable spaces</i> . Exception: Units that contain fewer than two <i>bedrooms</i> .								
	•				acc to at leact				
	404.4.3 Water closet accessibility. Every <i>bedroom</i> shall have access to at least one water closet and one lavatory without passing through								
	another bedroom. Every bedroom in a dwelling unit shall have access to at least one								
	water closet and lavatory located in the same story as the <i>bedroom</i> or an adjacent								
	story. 404.4.4 Prohibited occupancy. Kitchens and nonhabitable spaces shall not be								
	used for sleeping purposes.								
	404.4.5 Other requirements. <i>Bedrooms</i> shall comply with the applicable provisions of this code including, but not limited to, the light, <i>ventilation</i> , room area,								
	·			chapter; the plumb					
				er 5; the heating fac					
		acle requirements pe requirements o		d the smoke detector	or and				
	cinergency esca	ipe requirements o	i chapter 7.						
404.5	Dwelling	units shall not be	occupied by mor	e occupants than pe	rmitted hy the				
Overcrowding.		requirements of Ta	•						
			E 404.5 A REQUIREMENT	c					
		WINNING WI AREA	A NEQUINEIVIEIVI	5					
	MINIMUM AREA IN SQUARE FEET								
	SPACE	1-2 occupants	3-5 occupants	6 or more					
	Jr ACE			occupants					

, .		,	•						
	Living room ^{a, b}	120	120	150					
	Dining room ^{a, b}	No requirement	80	100					
	Bedrooms	Shall co							
	For SI: 1 square	quare foot = 0.093 m^2 .							
	a. See Section 404.5.2 for combined living room/dining room spaces.b. See Section 404.5.1 for limitations on determining the minimum occupancy area for sleeping purposes.								
	404.5.1 Sleeping area. The minimum occupancy area required by Table 404.5 shall not be included as a sleeping area in determining the minimum occupancy area for sleeping purposes. All sleeping areas shall comply with Section 404.4. 404.5.2 Combined spaces. Combined living room and dining room spaces shall comply with the requirements of Table 404.5 if the total area is equal to that required for separate rooms and if the space is located so as to function as a combination living room/dining room.								
* 404.6	404.6 Eff	i ciency unit. Nothir	ng in this section	shall prohibit an effi	ciency living				
Efficiency unit.	unit from meeting the following requirements:								
	1. A unit occupied by not more than one occupant shall have a minimum clear floor area of 120 square feet (11.2 m²). A unit occupied by not more than two <i>occupants</i> shall have a minimum clear floor area of 220 square feet (20.4 m²). A unit occupied by three <i>occupants</i> shall have a minimum clear floor area of 320 square feet (29.7 m²). These required areas shall be exclusive of the areas required by Items 2 and 3.								
	2. The unit shall be provided with a kitchen sink, cooking appliance and refrigeration facilities, each having a minimum clear working space of 30 inches (762 mm) in front. Light and <i>ventilation</i> conforming to this code shall be provided.								
		shall be provided avatory and bathtu		bathroom containing	g a water				
	4. The max	kimum number of a	occupants shall b	oe three.					
404.7 Food preparation.	and equipment	to store, prepare a	nd serve foods i	poses shall contain s n a sanitary manner. disposal of food was	There shall				

including facilities for temporary storage.

