

Occupancy	Occupancy Examples	Fire Alarm	Fire Sprinkler
All Except		Atrium connecting more than 2 floors	Basement >1,500 SF w/o opng w/in 75' off all pts
R3 and U		Lowest level of structure >60 below grade	with rdirect exit to grade.
(unless		Covered Mall Buildings	Rubbish and linen chutes
noted)		Central monitoring - (inc R3)	
		Special areas to be protected - SMC 17F.080.090	
>55 feet to		Tenant spaces exceeding 1,000 SF	Required
highest		Voice required	
floor from			
apparatus setup			
Day Cares		<=50 children - single station smoke detection	required if I occupancy
		>50 children - automatic	E and I occupancies
		>99 children - automatic/voice	
All A		Automatic >=300 people	Multiple fire areas share exits and combined exit
		Voice >=1000 people	load is 300 or more.
A1	Motion Picture Theaters	No manual pull stations required if sprinklered	Fire Area exceeds 12,000 SF
	Symphony/Concert Halls TV/Radio Studios	Automatic >100 above or below lowest level of egress	Occupant Load 300 or more Fire area on floor other than level of discharge -
			floor of and throughout all floors including the level
			of exit discharge.
	Theaters		Fire area contains multitheater complex
A2	Banguet halls	1	Floor area exceeds 5,000 SF
=	Night Clubs, taverns, bars		Occupant Load 100 or more
	Restaurants		Fire area on floor other than level of discharge -
			floor of and throughout all floors including the level
			Occupied roof >100 occupants - entire building
			of exit discharge.
A3	Amusement arcades, Art		Fire Area exceeds 12,000 SF
	galleries, bowling, churches,		Occupant Load 300 or more
	Gyms, Libraries, museums,		Fire area on floor other than level of discharge
	indoor pools, etc.		floor of and throughout all floors including the level
			of exit discharge.
A 4	A.rop.o.	4	Occupied roof >300 occupants - entire building Fire Area exceeds 12,000 SF
A4	Arenas Skating Rinks		Occupant Load 300 or more
	Swimming Pools		Fire area on floor other than level of discharge
	Tennis Courts		floor of and throughout all floors including the level
			of exit discharge.
			Occupied roof >300 occupants - entire building
A5	Bleachers, grandstands,	1	Concession stands, retail, press boxes and
	Stadiums		other accessory use areas > 1,000 SF
			Enclosed areas under bleachers < or equal to
			1,000 SF not 1-hour rated
			Enclosed areas under bleachers >1,000 SF
			Emergency voice/alarm caption >=15,000 occ.
В	Banks, barbers, clinic, >12th	Automatic >=500 people	Occupied roof >300 occupants - entire building Height of 55 FT or more
D	Grade, Labs, Post Offices, Pro-	Automatic >=100 people above or below exit level	
	fessional services, TV/Radio	Height of 55 FT or more	
	Stations, Offices	No manual pull stations required if sprinklered	
	Ambulatory health Care	Automatic	4 or more patients*
		No manual pull stations required if sprinklered	1 or more patients not at level of exit discharge*
E	6 or more persons thru 12th	Automatic - more than 50 occupants	Occupant load more than 50
-	grade, day care > 5 kids	Automatic/Voice - more than 100 occupants	Aggregate area exceeds 5,000 SF
		Exception for Manual Pulls (907.2.3)	Clustered portables unless exempt
F1	Moderate Hazard - appliances,	Automatic is required when the occupancy is two	Fire Area exceeds 12,000 SF
	bakeries, clothing, furniture,	Automatic is required when the occupancy is two or more stories in height	Fire Area is more than three stories above grade
1	Satonos, oloring, idriliule,		



Occupancy	Occupancy Examples	Fire Alarm	Fire Sprinkler
	printing, shoes, trailers, etc.	Automatic >500 persons above or below exit level No manual pull stations required if sprinklered	Combined fire area exceeds 24,000 SF Woodworking - >2,500 SF Upholstered furniture/mattresses >2,500 SF
F2	Low Hazard - beverages, brick foundries, ice, metal fab/assem		
H1	High Hazard - explosives, oxidizers, unstable materials		Automatic
H2	High Hazard - combustible dusts, flammable gases		
H3	High Hazard - Liquids <15 psi solids		
H4	Corrosives, highly toxic, toxic Materials	-	
H5	Semiconductor facilities	H5 - Automatic for highly toxic gases, organic peroxides, and oxidizers	Any building containing H5
11	Assisted Living Board and Care Congregate Care	Automatic Central manual pull allowed Sleeping areas to have single or multple station smoke detection	Any building containing I
12	Hospitals Nursing Homes Mental Hospitals Child Care 24 hr >5		
13	Prisons Jails Detention Facilities	Automatic (907.2.6.3.3)	
14	Day Care Facilities any age <24 hr >5 persons	Automatic - more than 50 occupants Automatic/Voice - more than 100 occupants Exception for Manual Pulls (907.2.3)	-
M	Department Stores, drug stores, markets, motor fuel dispensing, retail or whole- sale, sales rooms, open or closed malls.	Automatic >=500 people Automatic >=100 people above or below exit level Automatic >12,000 SF (SMC) No manual pull stations required if sprinklered	Fire Area exceeds 12,000 SF Fire Area is more than three stories above grade Combined fire area exceeds 24,000 SF High piled or rack storage arrays Display/sales of upholstered furniture > 5,000 SF
R1	Transient Boarding homes, hotels, motels	Automatic - 5 or more units/guest rooms Greater than two floors Not regd for 2 levels with each unit having direct exit	Any building containing R
R2	Apartment houses, dorms, boarding homes (not transient) frats and sororities, Hotels, Motels	No manual pull stations required if sprinklered ADA Type A-accessible communication features ADA Type B-prewired for building notification	
	Dorms and University residen- tial	Automatic Detection connected to building fire alarm system	
R3	Single family, duplex, child care <=5 persons <24 hr	Single/multiple station smoke alarms	
S1	Moderate Hazard - books, furniture, lumber, tires,		Fire Area exceeds 12,000 SF Fire Area is more than three stories above grade Commercial garage >5,000 Combined fire area exceeds 24,000 SF Upholstered furniture/mattresses > 5,000 SF
	Repair Garages Bulk Tire Storage		2 or more Floors exceeding 2,500 SF total area 1 story >12,000 SF Repair garage parking vehicles in basement Commercial vehicle repair >5,000 storage exceeds 20,000 SF
S2	Low Hazard - foods, metals, glass, parking garages, appliances	+	storage exceeds 20,000 SF Enclosed parking garages >12,000 SF Enclosed parking garage is below other groups - Except: garages below R3 occupancies Commercial garage >5,000